

PAD

Ac charging station

PE→ODA



Product features

Portable AC charging station can be carried in the car, charging at any time.

Product characteristics



Various charging modes



Delicate appearance



Multiple protection type



European electrical standards



Various methods of communication



Flexible and easy installation mode

Qingdao Penoda Electrical Co.,Ltd.

Room 308-8, 1577-10 Jinshui Road, Qingdao, Shandong, CN

T +86 15854513040 W www.penoda-power.com E jennifer@penoda-power.com

Specification

| Input and output | PAD-3 | PAD-7 |
|------------------------|---------------------|---------------------|
| The input voltage | 220V AC | 220V AC |
| Input frequency | 50Hz/60Hz | 50Hz/60Hz |
| The output voltage | 220V AC | 220V AC |
| Maximum output power | 3.5kW | 7kW |
| Maximum output current | 16A | 32A |
| Charging gun Type | Type 2 or Type1, 5m | Type 2 or Type1, 5m |
| The connector | Rob line charging | Rob line charging |

| Protective properties | | |
|-----------------------------|---|---|
| Over voltage protection | √ | √ |
| Under voltage protection | √ | √ |
| Overload protection | √ | √ |
| Short circuit protection | √ | √ |
| Electric leakage protection | √ | √ |
| Over temperature protection | √ | √ |
| Over temperature protection | √ | √ |

| Functions and Accessories | | |
|------------------------------|-----------------|-----------------|
| Liquid crystal display | √ | √ |
| Electric leakage protection | Type A | Type A |
| Charging mode | Plug and charge | Plug and charge |
| The LED light | √ | √ |
| Emergency stop button | √ | √ |
| Intelligent power regulation | optional | optional |

| Runtime environment | | |
|---------------------------|-----------------|-----------------|
| Protection grade | IP67 IK10 | IP67 IK10 |
| Working temperature | -25°C ~+50°C | -25°C ~+50°C |
| Relative humidity | 5%-95% | 5%-95% |
| The highest elevation | 2000m | 2000m |
| Cooling type | Natural cooling | Natural cooling |
| Standby power consumption | <8W | <8W |

| Product specification | | |
|-------------------------------|-------------------------------|-------------------------------|
| Size (width/height/thickness) | 240*103*60mm (pedestal mount) | 240*103*60mm (pedestal mount) |
| Weight | <4kg | <4kg |

| The installation accessories | | |
|------------------------------|-------|-------|
| Hanging bracket | √ | √ |
| Product certification | UL,CE | UL,CE |