

PAH-22-2-socket

AC+AC Charging station

PE → ODA



Product features

AC charging station is suitable for family/small business district, single gun or single socket output is optional

Product characteristics



Various charging modes



Delicate appearance



Multiple protection type



European electrical standards



Various methods of communication



Flexible and easy installation mode

Qingdao Penoda Electrical Co.,Ltd.

Room 308-8, 1577-10 Jinshui Road, Qingdao, Shandong, CN

T +86 15854513040 W www.penoda-power.com E jennifer@penoda-power.com

Specification

Input and output		PAS-22-2
The input voltage		380V AC
Input frequency		50Hz/60Hz
The output voltage		380V AC
Maximum output power		22kW *2
Maximum output current		32A*2
Charging gun Type		IEC 62196-2, Type2 socket*2 /16A standard EU sockets*2
The connector		Rob line charging

Protective properties	
Over voltage protection	√
Under voltage protection	√
Overload protection	√
Short circuit protection	√
Electric leakage protection	√
Over temperature protection	√
Over temperature protection	√

Functions and Accessories	
Liquid crystal display	√
Electric leakage protection	Type A + DC6mA (equivalent Type B)
Charging mode	APP/ swipe card/Plug and charge
The LED light	√
Emergency stop button	√
Intelligent power regulation	optional

Runtime environment	
Protection grade	IP54 IK10
Working temperature	-25°C ~+50°C
Relative humidity	5%-95%
The highest elevation	2000m
Cooling type	Natural cooling
Standby power consumption	<8W

Product specification	
Size (width/height/thickness)	1200*450*250MM (L*W*H) (pedestal mount)
Weight	<40kg

The installation accessories	
Hanging bracket	√
Product certification	CE