

# PAL

Ac charging station

# PE→ODA



## Product features

Single-phase AC charging station is suitable for family

### Product characteristics



Various charging modes



Delicate appearance



Multiple protection type



European electrical standards



Various methods of communication



Flexible and easy installation mode

Qingdao Penoda Electrical Co.,Ltd.

Room 308-8, 1577-10 Jinshui Road, Qingdao, Shandong, CN

T +86 15854513040 W [www.penoda-power.com](http://www.penoda-power.com) E [jennifer@penoda-power.com](mailto:jennifer@penoda-power.com)

# Specification

Input and output	PAL-3	PAL-7
The input voltage	220V AC	220V AC
Input frequency	50Hz/60Hz	50Hz/60Hz
The output voltage	220V AC	220V AC
Maximum output power	3.5kW	7kW
Maximum output current	16A	32A
Charging gun Type	Type 2 or Type1, 5m	Type 2 or Type1, 5m
The connector	Rob line charging	Rob line charging

Protective properties		
Over voltage protection	√	√
Under voltage protection	√	√
Overload protection	√	√
Short circuit protection	√	√
Electric leakage protection	√	√
Over temperature protection	√	√
Over temperature protection	√	√

Functions and Accessories		
Liquid crystal display	√	√
Electric leakage protection	Type A	Type A
Charging mode	swipe card/Plug and charge	swipe card/Plug and charge
The LED light	√	√
Emergency stop button	√	√
Intelligent power regulation	optional	optional

Runtime environment		
Protection grade	IP54 IK10	IP54 IK10
Working temperature	-25°C ~+50°C	-25°C ~+50°C
Relative humidity	5%-95%	5%-95%
The highest elevation	2000m	2000m
Cooling type	Natural cooling	Natural cooling
Standby power consumption	<8W	<8W

Product specification		
Size (width/height/thickness)	240*202*60mm (pedestal mount)	240*202*60mm (pedestal mount)
Weight	<10kg	<10kg

The installation accessories		
Hanging bracket	√	√
Product certification	CE	CE