

...Your form, fit & function provider

GF424A-5E

24 AWG, AEROSPACE ETHERNET CABLE



10/100BASE-T 2-PAIR ETHERNET CABLE

The GF424A-5E is designed to deliver 10/100Base-T Gigabit performance in accordance to ANSI/TIA-568-C.2 up to 268ft. The GF424A-5E is an identical alternative to PIC Wire's E10424. With a 100% foil and a 90% round wire braided shield, this design provides ample protection against EMI in the vast majority of applications. Product is sold in bulk or CAT5E tested assemblies. Please contact GIGAFLIGHT for a quote.

If your project requires a specific jacket color that is called out in the jacket color table, please contact us for availability.

CA	CABLE CONSTRUCTION				
1	Conductor	24 AWG Stranded SPC			
2	Insulation	Foamed, High-temp Fluoropolymer			
	Color Codes	Pair 1: White, Blue Pair 2: Green, Orange			
3	Shield 1	Composite Foil			
4	Shield 2	38 AWG Silver-plated Copper Braid			
5	Jacket	Translucent Blue Fluoropolymer			

JACKET COLORS & APPLICATIONS					
GF424A-5E	Translucent Blue	Standard			
GF424A-5E-0	Black	Secure Data			
GF424A-5E-1	White	Laser Markable			
GF424A-5E-2	Red	Secure Data			
GF424A-5E-3	Orange	Flight Test Data			

ENVIRONMENTAL & MECHANICAL PROPERTIES				
Shield Coverage	100% (Foil), 90% (Braid)			
Outer Diameter	0.21" (5.33 mm)			
Weight	33 lbs/1000 ft (49.11 kg/1000 m)			
Operating Temperature	-55°C to +200°C			
Minimum Bend Radius	1.1" (27.94 mm)			

ELECTRICAL PROPERTIES				
Impedance	100Ω			
Capacitance	13 pF/ft (42.65 pF/m)			
Velocity of Propagation	80%			
DC Resistance	28.5 Ω/1000 ft (93.5 Ω/1000 m)			
Dielectric Voltage Rating	1.5 kV RMS			
Max. Distance	268 ft (81.69 m)			
Attenuation (+25°C)	Frequency	dB/100 ft (m)		
	10 MHz	2.2 (7.2)		
	100 MHz	6.0 (19.7)		

CONNECTORS				
STYLE	P/N			
CAT5E Shielded RJ45 Straight Plug	GFSC-2025			

GIGAFLIGHT's aerospace cables are designed to be resistant to Skydrol, will meet requirements of RoHS & REACH, & meets Federal Aviation Regulations 14 CFR part 25.869 (a)(4), Appendix F part I (a)(3).

