

GF7-303D

26 AWG, LOW-LOSS HD VIDEO CABLE



HIGH-DEFINITION VIDEO CABLE

The GF7-303D is a form, fit, and function identical alternative for commonly used V76261. Meaning the electrical performance, size/weight, connector usage, and the applications are the same. The GF7-303D is not only recommended for use in SMPTE 259M, but also can be used in the SMPTE 292 and SMTPE 424 video applications.

This cable is currently available in two jacket colors, standard Laser Markable White and Flight Test Orange.

CABLE CONSTRUCTION

1	Center Conductor	26 AWG Stranded, Silver-plated Copper
2	Dielectric	Foamed, High-temp Fluoropolymer
3	Inner Shield	Composite Foil
4	Outer Shield	38 AWG Tin-plated Copper Braid
5	Jacket	White, Laser-markable Tefzel

ENVIRONMENTAL & MECHANICAL PROPERTIES

Outer Diameter	0.12" (3.05mm)	
Weight	11lbs/1000ft (16.37kg/1000m)	
Operating Temperature	-55°C to +150°C	
Minimum Bend Radius	0.64" (16.26mm)	
Max Len. SMPTE 292M HD-SDI	120ft (36.6m)	
Max Len. SMPTE 424M 3G-SDI	80 ft (24.4m)	

JACKET COLORS & APPLICATIONS

GF7-303D	White	Laser Markable
GF7-303D-3	Orange	Flight Test Data

ELECTRICAL PROPERTIES

Impedance	75Ω	
Capacitance	16 pF/ft (52.5pF/m)	
Velocity	80%	
DC Resistance	34.5 Ω/1000 ft (113.19 Ω/1000m)	
Time Delay	1.27 ns/ft (4.16 ns/m)	
Shield Effectiveness	>90 dB	
Attenuation (+25°C)	Frequency	dB/100 ft (m)
	135 MHz	5.8 (19.03)
	180 MHz	6.7 (21.98)
	270 MHz	8.3 (27.23)
	360 MHz	9.7 (31.82)
	400 MHz	10.2 (33.47)
	750 MHz	14.2 (46.59)
1500 MHz	20.6 (67.59)	
	3000 MHz	30.3 (99.41)

CONNECTORS

STYLE	P/N
75Ω M39029 Size 8 Pin	GF7-8P303HD
75Ω M39029 Size 8 Socket	GF7-8S303HD
75Ω M39029 Size 12 Pin	GF7-12P303HD
75Ω M39029 Size 12 Socket	GF7-12S303HD
BNC Straight Plug	GF7-BS303D

All tests performed in accordance with MIL-DTL-17
 GIGAFLIGHT's aerospace cables are designed to be resistant to Skydrol, will meet requirements of RoHS & REACH, & meets Federal Aviation Regulations 14 CFR part 25.869 (a)(4), Appendix F part I (a)(3).

