

...Your form, fit & function provider

GF824B-6A

24 AWG, CATEGORY 6A ETHERNET CABLE



CAT6A 10Gb ETHERNET CABLE

The GF824B-6A is designed to deliver 10 Gigabit performance in accordance to ANSI/TIA 568 Category 6A up to 246ft. The GF824B-6A is a suitable electrical alternative to the E6A6824 and MX10G-24. With a 100% foil and a 90% round wire braided shield, this design provides ample protection against EMI in the vast majority of applications. Product is sold in bulk or CAT6A tested assemblies. Please contact GIGAFLIGHT for a quote.

If your project requires a specific jacket color that is called out in the jacket color table, please contact us for availability.

CABLE CONSTRUCTION				
1	Conductor	24 AWG Stranded Silver-plated HSCA		
2	Insulation	Solid, High-temp Fluoropolymer		
	Color Codes	Pair 1: Blue, White/Blue Pair 2: Orange, White/Orange Pair 3: Green, White/Green Pair 4: Brown, White/Brown		
3	Spline	Foamed, High-temp Fluoropolymer		
4	Binder	PTFE Tape		
5	Shield 1	Composite Foil		
6	Shield 2	38 AWG Tin-plated Copper Braid		
7	Jacket	White, Laser-markable Tefzel		

ENVIRONMENTAL & MECHANICAL PROPERTIES					
0.262" (6.65 mm)					
47.5 lbs/1000 ft (70.69 kg/1000 m)					
-55°C to +150°C					
1.3" (33.02 mm)					

ELECTRICAL PROPERTIES						
Impedance	100Ω					
Capacitance	14.5 pF/ft (47.57 pF/m)					
Velocity of Propagation	70%					
DC Resistance	28.5 Ω/1000 ft (93.5 Ω/1000 m)					
Dielectric Voltage Rating	1.50 kV RMS					
Attenuation (+25°C)	Frequency	dB/100 ft (m)				
	10 MHz	2.2 (7.2)				
	100 MHz	6.8 (22.3)				
	250 MHz	10.9 (35.8)				
	500 MHz	15.6 (51.2)				

JACKET COLORS & APPLICATIONS						
GF824B-6A	White	Standard				
GF824B-6A-2	Red	Secure Data				
GF824B-6A-3	Orange	Flight Test Data				

CONNECTORS					
STYLE	P/N				
Standard RJ45 Straight Plug	GFSC-2006				
Ruggedized RJ45 Straight Plug, T568A	GFSC-2007				
Ruggedized RJ45 Right Angle Plug, T568A	GFSC-2008				
Ruggedized RJ45 Straight Plug, T568B	GFSC-2021				
Ruggedized RJ45 Right Angle Plug, T568B	GFSC-2022				

GIGAFLIGHT's aerospace cables are designed to be resistant to Skydrol, will meet requirements of RoHS & REACH, & meets Federal Aviation Regulations 14 CFR part 25.869 (a)(4), Appendix F part I (a)(3).

